



DUAL BAND FM TRANSCEIVER

IC-2725E

Twice the versatility, twice the fun!

V/V, U/U simultaneous receive capability

The IC-2725E is a unique dual band mobile, providing VHF/VHF, UHF/UHF simultaneous receive capability along with VHF/UHF full duplex operation. The simple touch of a button allows you to change the main (transmit) band and sub band.

Independent controls for each band

Operating two bands simultaneously is very simple with the symmetric layout and the wide LCD display showing both band settings in an easy to read side by side format. The IC-2725E provides separate tuning, volume, squelch knobs and function buttons for the left and right side bands. Also, listen to both bands independently through separate left and right band audio jacks.

Dynamic Memory Scan (DMS)

With 212 memory channels, Icom's exclusive Dynamic Memory Scan system gives you flexibility over your scanning lists, fully customizable into 10 banks.



Photo shows combined controller/main unit setup using MB-85.

Selectable Green and Amber Display.



Compact remote controller

The supplied MB-85 allows mounting of the controller on the main unit. The optional MB-84 with the OPC-1155, 3.5m separation cable offers the flexibility of mounting the controller, while placing the main unit in an out-of-the-way location. Microphone jacks are located on both the controller and the main unit.

HM-133, remote control microphone

The backlit HM-133, gives you control of your IC-2725E from the palm of your hand. The Icom exclusive "Hot keys" (F1/F2) memorize the transceiver's full settings. As if switching between two separate radios, VHF/UHF operating frequencies, tone settings as well as the display color and set mode settings are memorized.



HM-133

DTCS and CTCSS

The IC-2725E incorporates 104x2 DTCS and 50 CTCSS tone codes along with a tone scan function. Don't miss out on communications because of not having the proper type of "tones"! The "pocket beep" feature gives you an audible and visible indicator of an incoming call.

And more...

- 9600bps packet data terminal (mini-DIN 6-pin connector)
- 10dB RF attenuator
- Selectable squelch delay
- 14 DTMF memory channels (24 digits)
- Sub band auto mute function
- Wide/narrow channel spacing (Left side band only)
- Newly adopted MOS-FET power amplifier

Icom Inc.

SPECIFICATIONS

GENERAL

- Frequency coverage : (Unit: MHz)
 EUR version 144-146, 430-440
 ITR version 144-146, 430-434, 435-438
- Mode : FM
- Number of channels : 212 (Including 2 call and 10 scan edges)
- Antenna impedance : 50Ω (SO-239)
- Power supply requirement : 13.8V DC ±15%
- Usable Temp. range : -10°C to +60°C
- Frequency stability : ±10ppm (-10°C to +60°C)
- Tuning step increments : 5, 10, 12.5, 15, 20, 25, 30 and 50kHz
- Current drain (at 13.8V DC) :
 Transmit VHF 12A
 UHF 11A
 Receive Stand-by 1.2A
 Max. audio 1.8A
- Dimensions (projections not included; W×H×D) :
 Controller 140 × 50 × 24.5mm
 Main Unit 140 × 40 × 187mm
- Weight (approx.) :
 Controller 150g
 Main Unit 1.25kg

TRANSMITTER

- Output power (selectable):
 VHF 50W, 15W approx., 5W approx.
 UHF 35W, 15W approx., 5W approx.
- Max. freq. deviation : ±5.0/2.5kHz (wide/narrow)
- Spurious emissions : Less than -60dB
- Microphone impedance : 600Ω (8-pin modular jack)

RECEIVER

- Receive system : Double conversion superheterodyne
- Intermediate frequencies: 1st 38.85/46.05MHz (Left/right side band) 2nd 450/455kHz
- Sensitivity (at 12dB SINAD): Less than 0.18μV
- Squelch sensitivity : Less than 0.13μV (at threshold)
- Selectivity (Wide/Narrow) : More than 12/6kHz at -6dB
 Less than 30/20kHz at -60dB
- Spurious rejection ratio : More than 60dB
- Audio output (at 13.8V DC): More than 2.4W at 10% distortion with an 8Ω load
- Ext. speaker connector : 2-conductor 3.5 (d) mm/8Ω

Applicable U.S. Military Specifications

Standard	MIL 810 C		MIL 810 D		MIL 810 E		MIL 810 F	
	Method	Proc.	Method	Proc.	Method	Proc.	Method	Proc.
Low Pressure	500.1	I	500.2	I, II	500.3	I, II	500.4	I, II
High Temp.	501.1	I	501.2	I, II	501.3	I, II	501.4	I, II
Low Temp.	502.1	I	502.2	I, II	502.3	I, II	502.4	I, II
Temp. Shock	503.1	I	503.2	I	503.3	I	503.4	I
Solar Radiation	505.1	I	505.2	I	505.3	I	505.4	I
Rain	506.1	I	506.2	I	506.3	I	506.4	I
Humidity	507.1	I, II	507.2	II, III	507.3	II, III	507.4	-
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	-
Dust	510.1	I	510.2	I	510.3	I	510.4	I
Vibration	514.2	VIII, X	514.3	I	514.4	I	514.5	I
Shock	516.2	I, II, V	516.3	I, IV	516.4	I, IV	516.5	I, IV

Supplied accessories:

- Hand microphone, HM-133
- Combination bracket, MB-85
- DC power cable, OPC-1132
- 20cm Separation cable
- Spare fuse

All stated specifications are subject to change without notice or obligation.

OPTIONS

■ MOUNTING BRACKETS

- **MB-84** CONTROLLER BRACKET
 Mounts the remote controller in a convenient location for operation with the front panel detached.
- **MB-85** COMBINATION BRACKET
 Mounts the remote controller to the main unit. 20cm separation cable is supplied
- **MB-65** MOUNTING BASE
 Mounts the remote controller with the MB-84. Adjustable angle and direction for optimum positioning.
- **MB-17A** MOBILE MOUNTING BRACKET
 The main unit is easily attached and removed.



■ MICROPHONE ACCESSORIES

- **HM-118TN** DTMF MICROPHONE
 DTMF microphone.
- **HM-118N** HAND MICROPHONE
 Regular hand microphone.
- **HM-133** REMOTE CONTROL MICROPHONE
 Full remote control microphone with keypad back-lighting. Same as supplied.
- **OPC-440/OPC-647** MIC EXTENSION CABLES
 OPC-440: 5.0m ; OPC-647: 2.5m
- **OPC-589** MIC ADAPTER CABLE
 Allows you to connect an 8-pin microphone.



■ OTHER ACCESSORIES

- **CS-2720** CLONING SOFTWARE
 + **OPC-478/OPC-478U** CLONING CABLES
 OPC-478: RS-232C cable ; OPC-478U: USB cable
- **OPC-474** CLONING CABLE (between transceivers)
- **OPC-347/OPC-1132** DC POWER CABLES
 OPC-347: 7.0m; OPC-1132: 3.0m
- **OPC-441** SPEAKER EXTENSION CABLE
 5.0m speaker extension cable.
- **OPC-1155/OPC-1156** SEPARATION CABLES
 3.5m separation cable for remote controller. A modular connector is supplied with OPC-1156.
- **SP-7/SP-10** EXTERNAL SPEAKERS



Icom Inc. 1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.

2380 116th Avenue NE,
 Bellevue, WA 98004, U.S.A.
 Phone : +1 (425) 454-8155
 Fax : +1 (425) 454-1509
 E-mail : sales@icomamerica.com
 URL : <http://www.icomamerica.com>

Icom New Zealand

146A Harris Road, East Tamaki,
 Auckland, New Zealand
 Phone : +64 (09) 274 4062
 Fax : +64 (09) 274 4708
 E-mail : inquiries@icom.co.nz
 URL : <http://www.icom.co.nz>

Icom (UK) Ltd.

Unit 9, Sea St., Herne Bay,
 Kent, CT6 8LD, U.K.
 Phone : +44 (0)1227 741741
 Fax : +44 (0)1227 741742
 E-mail : info@icomuk.co.uk
 URL : <http://www.icomuk.co.uk>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road,
 Taipei, Taiwan, R.O.C.
 Phone : +886 (02) 2559 1899
 Fax : +886 (02) 2559 1874
 E-mail : sales@asia-icom.com
 URL : <http://www.asia-icom.com>

Icom Canada

Glenwood Centre #150-6165 Highway 17,
 Delta, B.C., V4K 5B8, Canada
 Phone : +1 (604) 952-4266
 Fax : +1 (604) 952-0090
 E-mail : info@icomcanada.com
 URL : <http://www.icomcanada.com>

Icom (Europe) GmbH

Communication Equipment
 Himmelgeister Str. 100,
 D-40225 Düsseldorf, Germany
 Phone : +49 (0)211 346047
 Fax : +49 (0)211 333639
 E-mail : info@icom-europe.com
 URL : <http://www.icomeurope.com>

Icom France S.a

Zac de la Plaine, 1,
 Rue Brindejone des Moulains BP 5804,
 31505 Toulouse Cedex, France
 Phone : +33 (5) 61 36 03 03
 Fax : +33 (5) 61 36 03 00
 E-mail : icom@icom-france.com
 URL : <http://www.icom-france.com>

Beijing Icom Ltd.

10C07, Long Silver Mansion, No.88, Yong Ding
 Road, Haidian District, Beijing, 100039, China
 Phone : +86 (010) 5889 5391/5392/5393
 Fax : +86 (010) 5889 5395
 E-mail : bjicom@bjicom.com
 URL : <http://www.bjicom.com>

Icom (Australia) Pty. Ltd.

A.B.N. 88 006 092 575
 Unit 1 / 103 Garden Road,
 Clayton VIC 3168 Australia
 Phone : +61 (03) 9549 7500
 Fax : +61 (03) 9549 7505
 E-mail : sales@icom.net.au
 URL : <http://www.icom.net.au>

Icom Spain S.L.

Ctra. de Gracia a Manresa Km. 14,750
 08190 Sant Cugat del Valles Barcelona, Spain
 Phone : +34 (93) 590 26 70
 Fax : +34 (93) 589 04 46
 E-mail : icom@icomspain.com
 URL : <http://www.icomspain.com>

Icom Polska

Sopot, 3 maja 54, Poland
 Phone : +48 (58) 550 7135
 Fax : +48 (58) 551 0484
 E-mail : icompolska@icompolska.com.pl
 URL : <http://www.icompolska.com.pl>



Your local distributor/dealer:

Point electronics

A- 1060 Wien, Stumpergasse 41 - 43

Tel.: +43/ 1/ 597 08 80/0

FAX: +43/ 1/ 597 08 80/40

www.point.at www.icom.at
mail@point.at