



VHF MARINE TRANSCEIVER

IC-M33

It really floats!

BUOYANT

Waterproof

1m depth for 30 minutes



Introducing the world's first*¹ 5W VHF marine transceiver that floats! If you drop the IC-M33 into water, the radio comes up to the surface so that you can easily retrieve it from out of the water. As the radio has a rugged waterproof body*², it will keep on working even after it has been submerged. Reliable marine communications that won't let you down in or out of your boat!


When actually floating, the base of the radio is level with the water surface.

*¹ First as a 5W VHF marine handheld transceiver as researched by Icom as of October 2006.

*² 1m depth for 30 minutes, equivalent to IPX7. The IC-M33 is not designed to be used under the water.

Easy to see LCD with large channel indication

The IC-M33 has an easy to see LCD (32x16 mm) with a clear 2-digit channel number indication. The Volume and SQL levels are shown in the display. LCD and key back-lighting is standard for night time operation.



Actual display size.

Easy to use, easy to hold

9 large buttons on the front panel provide simple straight forward operation. It Weighs only 305g, and the IC-M33's easy-to-hold rounded body fits comfortably in your hand.

Quick channel selection with Favourite channel function

Tag your favourite or often used channels then push the "Fav" button, and easily recall those channels, while ignoring un-tagged channels.

Li-Ion battery and charger standard

A Lithium-Ion battery pack and battery charger are supplied as standard. The BP-252 Lithium-Ion battery pack provides 9 hours* of operating time.

* Typical operation with Tx (Hi): Rx: standby=5:5:90

AquaQuake draining function

The AquaQuake draining function emits a vibrating sound and clears water away from the speaker grill.

Optional speaker-microphone, HM-165

The new optional waterproof speaker-microphone HM-165 will still allow the IC-M33 to float when attached. You will get great audio from it as well.

Other features

- Powerful 5W output power
- Dual/Tri-watch functions
- 4-step battery life indicator
- 2-step power saver
- 70 programmable channels
- Auto scan function
- Instant access to Ch 16 or programmable call channel
- Optional battery case for using with alkaline cells (Also floats when connected to the IC-M33)

SPECIFICATIONS

GENERAL

- Frequency range :
 - Marine Tx 156.000-161.450MHz
 - Rx 156.000-163.425MHz
- Usable channels : INT, USA* channels; (* Depending on version)
- Current drain (at 7.4V DC, approx.) :
 - Tx 5W output 1.5A
 - 1W output 0.7A
 - Rx AF max. 200mA typical
- Operating Temp. range : -15°C to +55°C
- Antenna impedance : 50Ω (STUD)
- Dimensions (W×H×D) : 62×141.5×43 mm (projections not included)
- Weight (approx.) : 305g (with BP-252, FA-SC58V and MB-109)

TRANSMITTER

- Output power : 5/1W
- FRG version 1/0.5W
- Max. frequency deviation : ± 5.0kHz
- Audio harmonic distortion: Less than 10% (at 60% dev.)
- Frequency error : ± 1.5kHz
- Spurious emissions : Less than 0.25µW
- Adjacent channel power : 70dB
- Hum and noise ratio : 40dB

RECEIVER

- Sensitivity (20dB SINAD) : -2dBµ emf typical
- Squelch sensitivity : -6dBµ emf typical (threshold)
- Adjacent Ch. selectivity : 70dB
- Spurious response : 70dB

- Intermodulation rejection : 68dB
- Hum and noise ratio : 40dB
- Audio output power : 0.2W (at 10% distortion with an 8Ω load)

Measurements made in accordance with EN301-178-2. All stated specifications are subject to change without notice or obligation.

Supplied accessories



- Battery pack, BP-252
- AC adapter, BC-174E*
- Antenna, FA-SC58V
- Battery charger, BC-173
- Belt clip, MB-109
- Hand strap

(* Not supplied depending on version.)

OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.



BP-251 BATTERY CASE
Battery case for AAA (LR03)×5 alkaline cells.
Output power: 2W.
BP-252 7.4V/980mAh Li-Ion BATTERY PACK
Provides 9 hours operating time (approx.).
(Typical operation with Tx (Hi): Rx: standby=5:5:90)



BC-173 DESKTOP CHARGER
+ **BC-174E AC ADAPTER**
Regularly charges the battery pack, BP-252 in 10 hours (approx.).



BC-162 DESKTOP CHARGER
+ **BC-145E/UK AC ADAPTER**
Rapidly charges the battery pack, BP-252 in 2 hours (approx.).



HM-165 SPEAKER-MICROPHONE
Waterproof construction equivalent to IPX7 (1 m depth for 30 min.).



MB-109 BELT CLIP
Alligator type.
Same as supplied.

Icom Inc. 1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.
2380 116th Avenue NE,
Bellevue, WA 98004, U.S.A.
Phone : +1 (425) 454-8155
Fax : +1 (425) 454-1509
E-mail : sales@icomamerica.com
URL : <http://www.icomamerica.com>

Icom New Zealand
146A Harris Road, East Tamaki,
Auckland, New Zealand
Phone : +64 (09) 274 4062
Fax : +64 (09) 274 4708
E-mail : inquiries@icom.co.nz
URL : <http://www.icom.co.nz>

Icom (UK) Ltd.
Unit 9, Sea St., Herne Bay,
Kent, CT6 8LD, U.K.
Phone : +44 (01227) 741741
Fax : +44 (01227) 741742
E-mail : info@icomuk.co.uk
URL : <http://www.icomuk.co.uk>

Asia Icom Inc.
6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone : +886 (02) 2559 1899
Fax : +886 (02) 2559 1874
E-mail : sales@asia-icom.com
URL : <http://www.asia-icom.com>

Icom Canada
Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone : +1 (604) 952-4266
Fax : +1 (604) 952-0090
E-mail : info@icomcanada.com
URL : <http://www.icomcanada.com>

Icom (Europe) GmbH
Communication Equipment
Himmelgeister Str. 100,
D-40225 Düsseldorf, Germany
Phone : +49 (0211) 346047
Fax : +49 (0211) 333639
E-mail : info@icomeurope.com
URL : <http://www.icomeurope.com>

Icom France s.a.s.
Zac de la Plaine,
1 Rue Brindejonn des Moulinais, BP 45804,
31505 Toulouse Cedex 5, France
Phone : +33 (5) 61 36 03 03
Fax : +33 (5) 61 36 03 00
E-mail : icom@icom-france.com
URL : <http://www.icom-france.com>

Icom (Australia) Pty. Ltd.
Unit 1 / 103 Garden Road,
Clayton VIC 3169 Australia
Phone : +61 (03) 9549 7500
Fax : +61 (03) 9549 7505
E-mail : sales@icom.net.au
URL : <http://www.icom.net.au>

Icom Spain S.L.
Ctra. Rubi, No. 88 "Edificio Can Castanyer"
08190, Sant Cugat del Valles, Barcelona, Spain
Phone : +34 (93) 590 26 70
Fax : +34 (93) 589 04 46
E-mail : icom@icomspain.com
URL : <http://www.icomspain.com>

Icom Polska
Sopot, 3 maja 54, Poland
Phone : +48 (58) 550 71 35
Fax : +48 (58) 551 04 84
E-mail : icompolksa@icompolksa.com.pl
URL : <http://www.icompolksa.com.pl>

Your local distributor/dealer:

Point electronics
A- 1060 Wien, Stumpergasse 41 - 43
Tel.: +43/ 1/ 597 08 80/ 0 FAX: DW 40
www.point.at mail@point.at