

Top Performance Mobile Airband Radio

with Active Noise Cancelling and Bluetooth® Wireless Connectivity



High Visibility, Simple Operation

The full dot-matrix LCD allows for high visibility and clearly shows alphanumeric characters and icons. Programming memory channels and other radio settings can be simply made from the front panel by radio users. These customizing functions can also be restricted, depending on the radio settings.

Optional Bluetooth® Headset Connectivity

With the optional UT-133A Bluetooth® unit, the IC-A120E can be used with a third-party wireless Bluetooth® headset. Also, using the optional VS-3 Bluetooth® headset, the side tone function is available.

Active Noise Cancelling (ANC)

The newly added built-in ANC reduces background noise in the received and transmitting signals. This function is effective in extremely noisy airport environments full of aircraft noise. The automatic noise limiter (ANL)* reduces pulse-type noise such as engine ignition.

* The ANL and ANC functions cannot be used at the same time.

IP54 Dust-Protection and Water Resistance

The IC-A120E has IP54 dust-protection and water resistance. This construction allows for use in open-air vehicles.

Dualwatch and ON-Hook Scan Functions

The dualwatch function checks the priority and operating channels alternatively. The ON-Hook scan function automatically starts scanning when the hand microphone is hooked on the microphone hanger. When you take the microphone OFF hook, the scanning stops at the priority channel or displayed channel (according to the pre-programming).

Side Tone Function

When using a third-party headset with the optional OPC-871A headset adapter, the side tone function allows you to monitor your own transmitted voice via the connected headset. Even when using a hand microphone, your voice can be monitored from the headset.

Optional Speaker-Microphone, HM-217

Listen to received audio through the HM-217's built-in speaker. From the speaker-microphone's front panel, access up/down buttons and two programmable buttons (P1/P2) which can be used as a shortcut to activate frequently used functions.

Other Features

- A total of 200 memory channels with 12-character channel names
- Both 12- and 24- volt systems compatible
- 8.33 kHz* and 25 kHz channel spacing
* For EUR version only
- 36W (P.E.P) RF output power
- Dualwatch and priority scan functions
- Power on password protection
- PC programming capability
- CI-V Commands for external control
- VE-PG3 RoIP gateway for interconnect with other radio devices
- Compliant with European E-marking for installation in vehicles

OPTIONS

Bluetooth® UNIT & Bluetooth® HEADSET




UT-133A **VS-3**
Use with UT-133A in a pair.

HAND MICROPHONES



HM-216 **HM-217**
Same as supplied. Speaker-microphone.

HEADSET ADAPTER



OPC-871A
To interconnect with a third-party aviation headset.

RoIP GATEWAY & CABLE



VE-PG3 **OPC-2275**
To interconnect with other radio devices.

SPECIFICATIONS

GENERAL		IC-A120E
Frequency range	EUR	118.000-136.992MHz
(Tx/Rx)	AUS	118.000-136.975MHz
Channel spacing	EUR	25kHz / 8.33kHz
	AUS	25kHz
Type of emission	EUR	6K80A3E, 5K00A3E
	AUS	6K80A3E
Operating temperature	-20°C to +55°C	
Antenna connector	SO-239 (50Ω)	
Number of memory channels	200 channels	
Power supply requirement	13.75V/27.5V DC	
Current drain	Tx	5.0A (maximum)
(at 13.75V)	Rx	4.0A (at AF max.), 0.5A (at stand-by)
Dimensions	161 (W) x 45 (H) x 175 (D) mm	
(Projections not included)	approximately	
Weight	1.5kg approximately (main unit)	
TRANSMITTER		
Output power (at 13.75V)	9.0W+1.5dB/-3dB (-20°C to +55°C)	
(Carrier Power)	9.0W±1.5dB (+15°C to +35°C)	
Frequency stability	±1ppm (0°C to +40°C)	
Spurious emissions*1	Less than -46dBm	
9kHz to 30MHz	Less than -36dBm/ Less than -46dBm*2	
30MHz to 1GHz	Less than -30dBm/ Less than -40dBm*2	
1GHz to 4GHz		
Microphone impedance	600Ω	
RECEIVER		
Intermediate frequencies	38.85MHz/450kHz (1st/2nd)	
Sensitivity (at 12dB SINAD)	Less than 1.8 μV (with CCITT filter)	
Selectivity	8.33kHz	2.778/7.37kHz (6dB/60dB)
	25kHz	8/25kHz (6dB/60dB)
Spurious response	More than 70dB	
Audio output power	(10% distortion, 60% modulation)	
Internal SP (8Ω load)	1.5W typical	
External SP (8Ω load)	More than 10W	
Headphone (500Ω load)	More than 100mW	

*1 Except for operating frequency ±1MHz. *2 For Harmonics/Non-harmonics. Measurements made in accordance with EN 300 676-1. All stated specifications are subject to change without notice or obligation.

Applicable U.S. Military Specifications

Standard	MIL 810 G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Humidity	507.5	II
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Applicable IP Rating

Ingress Protection Standard	
Dust & Water	IP54 (Dust-protection and water resistance)

Supplied Accessories

- Hand microphone, HM-216
- DC power cable
- Mounting bracket kit
- Microphone hanger kit
- Fuses

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand, and/or other countries. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Icom Inc. is under license. All other trademarks are the properties of their respective holders.

Icom Inc. 1-1-32, Kami-minami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 www.icom.co.jp/world **Count on us!**

Icom America Inc.
12421 Willows Road NE,
Kirkland, WA 98034, U.S.A.
Phone: +1 (425) 454-9155
Fax: +1 (425) 454-1509
E-mail: sales@icomamerica.com
URL: <http://www.icomamerica.com>

Icom (Europe) GmbH
Communication Equipment
Auf der Krautweide 24
65812 Bad Soden am Taunus, Germany
Phone: +49 (6196) 76685-0
Fax: +49 (6196) 76685-50
E-mail: info@icomeurope.com
URL: <http://www.icomeurope.com>

Icom France s.a.s.
Zac de la Plaine,
1 Rue Brindejone des Moulinais, BP 45804,
31505 Toulouse Cedex 5, France
Phone: +33 (5) 61 36 03 03
Fax: +33 (5) 61 36 03 00
E-mail: icom@icom-france.com
URL: <http://www.icom-france.com>

Asia Icom Inc.
6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone: +886 (02) 2559 1899
Fax: +886 (02) 2559 1874
E-mail: sales@asia-icom.com
URL: <http://www.asia-icom.com>

Your local distributor/dealer:

Icom Canada
Glenwood Centre #150-6165
Highway 17A, Delta, B.C.,
V4K 5B8, Canada
Phone: +1 (604) 952-4266
Fax: +1 (604) 952-0090
E-mail: info@icomcanada.com
URL: <http://www.icomcanada.com>

Icom Spain S.L.
Ctra. Rubi, No. 88 "Edificio Can Castanyer"
Bajos A 08174, Sant Cugat del Valles,
Barcelona, Spain
Phone: +34 (93) 590 26 70
Fax: +34 (93) 589 04 46
E-mail: icom@icomspain.com
URL: <http://www.icomspain.com>

Icom (Australia) Pty. Ltd.
Unit 1 / 103 Garden Road,
Clayton, VIC 3168 Australia
Phone: +61 (03) 9549 7500
Fax: +61 (03) 9549 7505
E-mail: sales@icom.net.au
URL: <http://www.icom.net.au>

Shanghai Icom Ltd.
No.101, Building 9, Caifuxingyuan Park,
No.188 Maoting Road, Chedun Town,
Songjiang District, Shanghai, 201611, China
Phone: +86 (021) 6153 2768
Fax: +86 (021) 5765 9987
E-mail: bjicom@bjicom.com
URL: <http://www.bjicom.com>

Point electronics
A- 1060 Wien, Stumpergasse 43
Tel.: +43 / 1 / 597 08 80
www.point.at mail@point.at

Icom Brazil
Rua Itororó, 444 Padre Eustáquio
Belo Horizonte MG,
CEP: 30720-450, Brazil
Phone: +55 (31) 3582 8847
Fax: +55 (31) 3582 8987
E-mail: sales@icombrasil.com

Icom (UK) Ltd.
Blacksloe House, Altira Park,
Herne Bay, Kent, CT6 6GZ, U.K.
Phone: +44 (0) 1227 741741
Fax: +44 (0) 1227 741742
E-mail: info@icomuk.co.uk
URL: <http://www.icomuk.co.uk>

Icom New Zealand
39C Rennie Drive, Airport Oaks,
Auckland, New Zealand
Phone: +64 (09) 274 4062
Fax: +64 (09) 274 4708
E-mail: inquiries@icom.co.nz
URL: <http://www.icom.co.nz>